

# 60cm Slide-out Rangehood

**MODEL / ASL60DR2S**

## FEATURES

440m<sup>3</sup>/hr extraction  
LED lighting  
Aluminium grease filters  
Ducted or recirculating installation options  
Stainless steel fascia included  
2 speed settings

## ACCESSORIES

120mm Flue outlet adapter  
2 Fascia rails included:  
> 40mm for ducted installation  
> 80mm for recirculating installation

## OPTIONAL ACCESSORIES

Carbon Filter - CP120

## PERFORMANCE FEATURES

440 m<sup>3</sup>/hr extraction  
Motor type:  
> Centrifugal  
Decibel rating (dBA) max:  
> 49-65 dBA

## CLEANING

Dishwasher safe aluminium grease filters

## EAN

9349260002593

## PRODUCT DIMENSIONS

Packaged (w, d, h mm)  
> 650 × 227 × 360mm  
Physical (w, d, h mm)  
> 599 × 278–472 × 176mm  
Weight (Gross/Net)  
> 9.2/8.1kg

## REQUIREMENTS

Supplied with 10 amp plug  
Rated voltage:  
> 220-240V, 50/60 Hz

## INSTALLATION

See below diagram



ALL INALTO PRODUCTS COME WITH A 2 YEAR WARRANTY. AUSTRALIAN CUSTOMERS ARE ELIGIBLE TO RECEIVE 1 EXTRA YEAR FOR FREE, SIMPLY REGISTER ONLINE WITHIN 90 DAYS OF PURCHASE

[WWW.INALTO.HOUSE/REGISTRATION](http://WWW.INALTO.HOUSE/REGISTRATION)

